

PF4000HH

Specification Sheet



The PF4000 turnstile (shown left) can be custom

made to suit your requirements. The example shown left was a 3/4 height turnstile made to fit into shipping containers with bio-metric access control and iris recognition specifically for the olympics.

- *Automatic drop arm*
- *Servo assist*
- *Motorised arm reset*



The PF4000HH Half Height Turnstiles

The PF4000HH Turnstile is ideal for settings where control of footfall in low or high usage areas is paramount. They are available as single or double alternatives.

The new PF4000 multi-functional half height turnstiles are an ideal solution for a variety of modern applications. Constructed from mild or stainless steel for long lasting and maintenance free performance, the PF4000s incorporate the very latest in modern design and styling to ensure maximum convenience and ease-of-use.

A wide range of access control system options are also available such as card, push button intercom or keypad, providing secure entry and exit for restricted areas.

The PF4000s can be powder coated to customer specification.

Options include automatic or manual drop arms for power failure. Directional Indicators (red/green) are included as standard.

We can also provide a full Site Preparation and Installation Service to client specification.

EVERY EFFORT HAS BEEN MADE IN PREPARATION OF THIS SHEET HOWEVER WE HOLD NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.

PF4000FH Specification Sheet



Card reader screen already integrated



Bright LED indication lights



Collapsible Arm in power failure



Don't forget to ask about all the different access control kit that we can supply. In

the majority of scenarios we will pre fit this equipment with your order cutting down the labour time on site. We offer endless combinations of access control.



Remember that we offer Full - Height turnstiles as well .

Our range currently consists PF4000HH (half height range), PF4000FH (full height

range), Disabled access gates and 3/4 height turnstiles. They are all available in both single and double and have been designed with strength thus allowing high volume usage. All have different advantages and niche applications so for the best advice give us a call on:

Power supply:
220V+ 10% 50/60 Hz, 2A.
(Absorbed load 30 W)

Arms and body:
Stainless Steel

Dimensions:
Single: 1235 x 1000 x 280
Arm: 500 (Walkway 530 to 550)

Duty Cycle:
100%

Operation temperature:
-20° +55° C

Flow Rate:
20 to 26 /min in a single direction

•Key Points:

- Communication: RS232 socket, LAN socket
- Directional indicator lights
- No passage time. (Adjustable)
- Provision for proximity readers

behind flush plexiglass (subject to size)

-
- Stainless steel body
- Stainless steel lid
- Stainless steel arms
- Can be easily integrated with railings/barriers providing the same look and feel throughout the desired area
- Operation: Bi-directional.
- Movement: Motorised – Servo Assist
- Fail safe (automatic drop arm)
- Motorised automatic reset of arms on power up (with obstruction sensing to stop arm lifting)

Options for access control:

- Keypad
- Proximity Cards
- Voice/Video Intercom Access
- Token Acceptors
- Remote Control Fobs
- Key switch

EVERY EFFORT HAS BEEN MADE IN PREPARATION OF THIS SHEET HOWEVER WE HOLD NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.