



Traffic Calming Speed Ramps



50 or 75mm Speed Ramp

The design offers early visual warning and provides a highly effective method of restricting speed. The speed ramp is available in two heights, consequently applying a set speed restriction, with the 50 mm version reducing vehicles to speeds of 15-20 mph. The 75mm version to speeds of 5-10 mph. The PF5750 can be laid in multiple lengths by simply interlocking each of the 500mm wide sections securely with four fixing bolts for extra stability. The 75mm option also includes a centre run cable tunnel for temporary traffic lights, fair grounds, water supplies etc. It is recommended that signage is used in conjunction with speed ramps to warn on coming traffic.

PF5750

- 1 **Interlocking** - Each section has an integral interlocking facility for ease of siting and installation
- 2 **Reflectors** - Each inner section has incorporated white reflectors for extra visibility
- 3 **Hose/Cables Channel** - 40mm x 25mm channel on the underside allowing for hose/cables to be located in
- 4 **Pre-Drilled Bolt Holes** - All sections are pre - formed ready for inserting coach bolts supplied ensuring they sit below the surface
- 5 **Non Slip** - Grooved surface increases friction to assist with grip of vehicle tyres
- 6 **Black/Yellow** - Sections are available please specify when ordering which colours you require



Specification:

- Traffic calming speed ramp

Product material:

- Recycled pvc

Weight:

- Ends cap 2.7kg mid section 8.6kg

Fixings:

- Universal fixings for tarmac or concrete (supplied)
- Central segments require 4no bolts
- End caps require 2no bolts

Key features:

- Package included end caps, mid sections and fixings
- Integral cable trunk
- Non-slip textured surface
- Embedded cats eyes as standard
- High visibility yellow sections contrasting with pure black sections

